

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
1 November 2001 (01.11.2001)

PCT

(10) International Publication Number  
**WO 01/81269 A1**

(51) International Patent Classification<sup>7</sup>: C04B 35/46,  
H01B 3/12

[KR/KR]: 6-803 Taeneung-Woosung Apt., Kongneung  
2-Dong, Nowon-Ku, Seoul 139-242 (KR). KIM, Hyo-Tae  
[KR/KR]: 36, KIST Dormitory, 39-1 Hawolgok-Dong,  
Sungbook-Ku, Seoul 136-791 (KR).

(21) International Application Number: PCT/KR00/00983

(22) International Filing Date: 30 August 2000 (30.08.2000)

(74) Agent: PARK, Jang-Won; 5th Floor, Jewoo Building,  
200, Nonhyun-Dong, Kangnam-Ku, Seoul 135-010 (KR).

(25) Filing Language: Korean

(26) Publication Language: English

(81) Designated States (*national*): CN, IN, JP, US.

(30) Priority Data:  
2000-21259 21 April 2000 (21.04.2000) KR

(84) Designated States (*regional*): European patent (AT, BE,  
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,  
NL, PT, SE).

(71) Applicant (*for all designated States except US*): KOREA  
INSTITUTE OF SCIENCE AND TECHNOLOGY  
[KR/KR]: 39-1, Hawolgok-Dong, Sungbook-Ku, Seoul  
136-791 (KR).

Published:

— with international search report


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): KIM, Yoon-Ho

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

MAA  
7/20/01

(54) Title: LOW TEMPERATURE SINTERABLE AND LOW LOSS DIELECTRIC CERAMIC COMPOSITIONS AND METHOD THEREOF



(57) Abstract: A low loss high-frequency dielectric ceramic composition for sintering at a low temperature and method of manufacturing the same which is characterized in that excellent dielectric properties such as a much lower sintering temperature and higher quality coefficient and dielectric constant, compared to a conventional high-frequency ceramic composition, a stabilized temperature coefficient, and a temperature compensating property varied according to a composition, are implemented using a low-priced material such as ZnO-MO ( $M=Mg, Co, Ni$ ) -  $TiO_2$ . In addition, Ag, Cu, an alloy thereof, or an Ag/Pd alloy can be used as an internal electrode. Thus, the composition of the present invention can be used as a dielectric material for all sorts of high-frequency devices, such as a stacked chip capacitor, stacked chip filter, stacked chip capacitor/inductor composite device and module, low temperature sintered substrate, resonator or filter and ceramic antenna.